



**Traceless™ - HPL - type 128, 138,
Compact (31 finish only) - type 568, 572,
575 & 590
Wilsonart**

Final Assembly: Temple, Texas, USA; Fletcher, North Carolina, USA

Life Expectancy: 20 - 50 Year(s)

Embodied Carbon: HPL:1.99E+00 kg CO2 eq.,

Compact:2.91E+01 kg CO2 eq. ■

Declared Unit: One square meter of product

End of Life Options: Landfill (100%)

EU CoC Screened: Does Not Contain

Ingredients:

Traceless™: Wood / Cellulose Fiber (Kraft / Decorative / Overlay); Melamine Resin¹; Phenolic Resin¹; Colorant; Grit; Pentaerythritol, ethoxylated, esters with acrylic acid (>1 - <8,5 mol EO); 1H-Isoindole-1,3(2H)-dione, 4,5,6,7-tetrachloro-2-[2-(4,5,6,7-tetrachloro-2,3-dihydro-1,3-dioxo-1H-inden-2-yl)-8-quinoliny]-; C. I. Pigment Blue 15; C.I. Pigment Black 28; Iron hydroxide oxide (Fe(OH)O); Pigment Red 254 (primary CASRN is 84632-65-5); Titanium dioxide; oxybis(methyl-2,1-ethanediyl) diacrylate; Trimethylolpropane Triacrylate/2-Hydroxypropyl Acrylate; Release

¹LBC Temp Exception RL-009 - Formaldehyde

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|--|-----------------------------|
| ☐ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ■ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Product Available with FSC Chain of Custody

WIL-0008
EXP. 01 JUN 2026
SCREENED: 24 JUN 2025
Original Issue Date: 2023